



WINTRADE S.r.l.
CHROME PLATED BARS • STEEL TUBES • SPECIAL STEELS

Cold drawn tube BK+S

*Ready for honing or skiving and
roller-burnishing inside outside*

According to EN 10305-2 / 10305-1

Steel Grade: E355 / ST-52.3

Chemical analysis

EN 10305-2

EN 10305-1

C	Mn	Si	P	S	Al
≤0,22	≤1,60	≤0,55	≤0,025	≤0,025	≤0,020
≤0,22	≤1,60	≤0,55	≤0,025	≤0,025	≤0,020

Mechanical properties at room temperature

	Heat treatment	Rp0,2 min. N/mm ²	Rm N/mm ²	A min. %	AvRT J	HB
EN 10305-2	+SR	435	590	10	-	-
EN 10305-1	+SR	450	580	10	-	-

Internal diameter tolerance: Up to - 0,2 a - 0,65 mm (according diameter)

Outside diameter tolerance: EN 10305-2 / 10305-1

Thickness tolerance: + / - 3%

Straightness: 1:1000 mm

Diameter range: outside diameter 20- 300 mm

Thickness Range: 5 / 6 / 7,5 / 10 / 12,5 / 15 / 17,5 / 20 / 25 mm

Bars length : 4000 / 12.000 mm

Eddy current test: 100% checked found ok

Marking: Dimension - Heat treatment- Steel grade- Heat number & Logo

Packaging: oil, caps

General properties and applications

Cold Drawn Tube BK+S is seamless / welded cold-drawn precision steel tube.

The inside diameter tolerances could be designed for either honing or skiving and roller-burnishing.